



O GAUGE

S 70-00 SMALL LINESIDE OFFICE WITH S 70-02 OFFICE INTERIOR

BUILD TIME APPROX 3 HOURS

PAINTING TIME APPROX 6 HOURS

GLUE USED:

- GORRILLA WOOD GLUE
- SUPERGLUE FOR PAINTED PARTS
- EVERBUILD CONTACT ADHESIVE FOR GLAZING

PAINTS USED:

- MODEL SPRAYED WITH POLYURETHANE YACHT VARNISH FROM A RATTLE CAN
- PHEONIX PRECISION PAINTS P953. DARK RED BRICK USED AS BASE BRICK COLOUR
- HUMBROL MATT 98 FOR WINDOW AND DOOR ARCHES

- HUMBROL MATT WHITE SPRAYED ON WINDOWS
- DOOR PAINTED WITH HUMBROL MATT 94
- HUMBROL MATT 98, 82, 100, 153 FOR INDIVIDUAL BRICKS
- REVELL ACRYLIC WHITE USED AS MORTAR COLOUR. APPLIED WITHOUT DILUTING AND THEN WIPED OFF WITH KITCHEN CLOTH. RECOMMEND TO PAINT THE MODEL WITH GLOSS VARNISH (POLYURETHANE YACHT VARNISH FROM A RATTLE CAN) PRIOR TO APPLYING MORTAR COLOUR TO AVOID COLOUR MIXING.
- MODEL SEALED WITH RAILMATCH MATT VARNISH
- THIN CELLOPHANE FOIL USED AS GLAZING
- ROOF BASE PAINTED WITH HUMBROL BROWN AND THEN DRY BRUSHED WITH RAILMATCH LMS FREIGHT GREY